

Product Data Sheet

GWJ2102W

JOINON Range

	CERIED	0
	(i=1)	e
)		6
		e

The wall-mounted I-ON charging stations are the JOINON solutions for public and semi-public access, designed for charging electric vehicles and to withstand any wear including impacts, stress, vandalism and atmospheric agents. They are the first and only on the market guaranteed with a IP55 protection rating. The special design allows the units to be adapted into any urban context and parking configuration, with a targeted focus on the user experience of drivers. They are available with standard JoinOn graphics, which may be customised on request.

INPUT	-	Socket/Connector Nr. (Type)	2 (Type 2 vandal-proof socket, with shutters)
Terminal blocks	2 x (5 x 10 mm²)	Charging activation	Remotely managed, via OCPP 1.6J
Nominale	32 A	Human Interface	LED RGB and TFT Display
stroom			
Total power	22 Kilowatt	Connectivity	LAN,WIFI,4G
OUTPUT	-	MECHANICAL FACTS	-
Nominale	400 V	Mounting and installation	Wall mount
spanning			
Kleur	Grey, Headboard RAL 7011	Voeding	11 kW per socket
		max.	
Materiaal	Steel sheet	Thermal-magnetic protection	Currently not present
External treatments	Anti-corrosion and anti-graffiti	Type aardlekbeveiliging	Currently not present
IP-	IP55	Power meter	Yes (Type MID)
graad			
Stoot-	IK10	DC Leakage check	Currently not present
bestendigheid			
Bedrijfstemperatuur	-25 +50 °C	(Auto)restart electrical protections	Currently not present
Customizations	Yes (front)		

DIMENSIONAL



TECHNICAL SYMBOLOGY



IP55

STANDARDS/APPROVALS

IK10



GEWISS S.p.A. Via A. Volta, 1 24069 Cenate Sotto - Bergamo - Italy tel. +39 035 94 61 11 fax +39 035 94 69 09 www.gewiss.com sat@gewiss.com Last update 20/04/2024 Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice