

Product Data Sheet

GWJ5001B

JOINON Range



Type 2 socket, compliant to IEC 62196-1 and IEC 62196-2 regulations, made for IEC 618581 regulation compliant EV charging, equipped with security shutters (IPXXD protection), double drain system for water, vandal-proof mechanism made by gate-valves that avoid unauthorized users to access electrical parts and by a locking actuator that has the double aim to block gate-valves and to lock the plug during the charging session. Gate-valves are opened by the insertion of the plug in the socket; they are automatically closed as long as the plug is removed at the end of each charging session. This socket is equipped with three microcontacts that check wether valves are opened or closed and wether locking actuator is engaged or not. Socket with rear cable entry.

Kleur	Zwart	Electrical protection	IPXXD
Aantal polen	5 (L, N, PE, CP, PP)	Stoot-	IK10
·		bestendigheid	
Nominale	32 A	IP-	IP55 (w/o plug inserted)
stroom		graad	
Nominale	200-250 V (power supply) / 0-30 V (CP, PP)	Thermospanning met kogel	125°C (active parts) / 80°C (passive parts)
spanning			
Nominale	50/60 Hz	Gloeidraadproef	850°C (active parts) / 960°C (external parts)
frequentie (Hz)			
Locking actuator parameters	-	Isolatiespanning (Ui)	500 V
Voltage Range	9-15,5 V	Opslagtemperatuur	-40 +70 °C
No load current	≤ 250 mA	Aanspanvermogen aansluitklem	2,5-10 mm² (power supply) 0,75-1,5 mm² (CP, PP)
		flexibele kabels (mm²)	
Working voltage	12 V	Bedrijfstemperatuur	-30°C ÷ +50 °C
Peak Current	3.2 A	MTTF	>10.000 insertions with no load
External self-extinguishing degree	V0 (UL94)		

DIMENSIONAL





TECHNICAL SYMBOLOGY









IK10

IP55 (w/o plug

125°C (active parts) / 850°C (active parts) / 80°C (passive parts) 960°C (external parts)

STANDARDS/APPROVALS







