




Type 2 socket, compliant to IEC 62196-1 and IEC 62196-2 regulations, made for IEC 61851 regulation compliant EV charging, equipped with security shutters (IPXXD protection), double drain system for water and a locking actuator that locks the plug during the charging session. Gate-valves are opened by the insertion of the plug in the socket; they are automatically closed as long as the plug is removed at the end of each charging session. This socket is equipped with three micro-contacts that check whether valves are opened or closed and whether locking actuator is engaged or not. Socket with rear cable entry.

Kleur	Zwart	Electrical protection	IPXXD
Aantal polen	7 (L1, L2, L3, N, PE, CP, PP)	Stootbestendigheid	IK10
Nominale stroom	32 A	IP- graad	IP55 (w/o plug inserted)
Nominale spanning	380-480 V (power supply) / 0-30 V (CP, PP)	Thermospanning met kogel	125°C (active parts) / 80°C (passive parts)
Nominale frequentie (Hz)	50/60 Hz	Gloeidraadproof	850°C (active parts) / 960°C (external parts)
Locking actuator parameters	-	Isolatiespanning (Ui)	500 V
Voltage Range	9-15,5 V	Opslagtemperatuur	-40 +70 °C
No load current	≤ 250 mA	Aanspanvermogen aansluitklem flexibele kabels (mm ²)	2,5-10 mm ² (power supply) 0,75-1,5 mm ² (CP, PP)
Working voltage	12 V	Bedrijfstemperatuur	-30°C + +50 °C
Peak Current	3.2 A	MTTF	>10.000 insertions with no load
External self-extinguishing degree	V0 (UL94)		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IK

IK10

IP

IP55 (w/o plug inserted)



125°C (active parts) / 850°C (active parts) /
80°C (passive parts) 960°C (external parts)

GWT

STANDARDS/APPROVALS

**UK
CA**



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 18/04/2024

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice