


Flush-mounting axial one-way switch module. An axial push-buttons on the front for switching an ON/OFF load (bistable/momentary function) or a timed ON load via an output contact with potential. The device must be completed with the front buttons key available. The device has N°3 DIP-switches, located on the back of the device, for feature configuration.

Omschrijving	Axial one-way switch module	Voeding	100 ÷ 240 V ac - 50/60 Hz
Aantal modules	2	Aantal ingangskanalen	2
Local control	Via 2 front push buttons (to complete with button key)	Auxiliary input channel voltage	100 ÷ 240 V ac - 50/60 Hz
Opslagtemperatuur	-25 ÷ +70 °C	N. of LED input channels	-
Bedrijfstemperatuur	-5 ÷ +45 °C	LED input channels voltage	-
Relative humidity (non-condensative)	Max 93%	Aantal uitgangskanalen	1
Front light signaling	Blauwe led	Uitgang contacten	1 NO 5A (AC1) 240 V ac
Aansluitklemmen voor bekabeling	Met schroef	240 V ac Incandescent-halogen lamps	Max 1000 W
Aanspanvermogen aansluitklem flexibele kabels (mm <sup>2</sup> )	Max. 1,5	240 V ac LED lamps	Max 100 W (max 5 lamps)
Aanspanvermogen aansluitklem starre kabels (mm <sup>2</sup> )	Max. 1,5	Loads piloted from electronic transf. 240 V ac	Max 250 VA
Context	Dry indoor places	240 V Fluorescent lamps	Max 120 W (max 6 lamps)
IP-graad	IP20 (with button key)	Load control	-
Standaard	2014/35/EU (LVD), 2014/30/EU (EMC), 2011/65/EU + 2015/863 (RoHS), EN 60669-2-1, EN 60669-1, EN IEC 63000		

## DIMENSIONAL



## TECHNICAL SYMBOLOGY

### IP

IP20 (with button key)

## STANDARDS/APPROVALS



