




Flush-mounting axial roller shutter module. Device for commanding the motor that drives roller shutters, curtains, Venetian blinds, roller blinds, etc. via 2 interlocked output contacts with potential. Two axial push-buttons on the front for upward (UP) and downward (DOWN) movement, and for regulating the tilt of the slats.

The device must be completed with the front buttons key available.

The device has n°3 DIP-switches, located on the back of the device, for feature configuration.

Omschrijving	Axial roller shutter module	Voeding	100 ÷ 240 V ac - 50/60 Hz
Aantal modules	1	Aantal ingangskanalen	2
Local control	Via 2 front push buttons (to complete with button key)	Auxiliary input channel voltage	100 ÷ 240 V ac - 50/60 Hz
Opslagtemperatuur	-25 ÷ +70 °C	N. of LED input channels	-
Bedrijfs-temperatuur	-5 ÷ +45 °C	LED input channels voltage	-
Relative humidity (non-condensative)	Max 93%	Aantal uitgangskanalen	2
Front light signaling	Blauwe led	Uitgang contacten	n. 2 x 2,3 A cosφ 0,6
Aansluitklemmen voor bekabeling	Met schroef	240 V ac Incandescent-halogen lamps	-
Aanspanvermogen aansluitklem flexibele kabels (mm <sup>2</sup> )	Max. 1,5	240 V ac LED lamps	-
Aanspanvermogen aansluitklem starre kabels (mm <sup>2</sup> )	Max. 1,5	Loads piloted from electronic transf. 240 V ac	-
Context	Dry indoor places	240 V Fluorescent lamps	-
IP-graad	IP20 (with button key)	Load control	-
Standaard	2014/35/EU (LVD), 2014/30/EU (EMC), 2011/65/EU + 2015/863 (RoHS), EN 60669-2-1, EN 60669-1, EN IEC 63000		

## DIMENSIONAL



## TECHNICAL SYMBOLOGY

### IP

IP20 (with button key)

## STANDARDS/APPROVALS



