


Flush-mounting auxiliary touch module with one command.

Two touch areas on the front, this product can be used in combination with the auxiliary wired inputs of the following devices of the Chorusmart range: connected commands, connected 1- channel On/Off actuator, connected movement sensors, TOUCH and EVO commands, or as a wired command for a connected 2-channel ZigBee interface.

The device must be completed with one of the ICE Touch plates available. Inside the package of the plates is a sheet of interchangeable icons to customize the control symbol.

Omschrijving	Auxiliary touch 1-command module	Voeding	100 ÷ 240 V ac - 50/60 Hz
Aantal modules	1	Aantal ingangskanalen	-
Local control	Via 2 frontal touch areas (must be completed with ICE Touch plate)	Auxiliary input channel voltage	-
Opslagtemperatuur	-25 ÷ +70 °C	Aantal uitgangskanalen	1
Bedrijfstemperatuur	-5 ÷ +45 °C	Uitgang contacten	-
Relative humidity (non-condensative)	Max 93%	240 V ac Incandescent-halogen lamps	-
Front light signaling	Blauwe led	240 V ac LED lamps	-
Aansluitklemmen voor bekabeling	Met schroef	Loads piloted from electronic transf. 240 V ac	-
Aanspanvermogen aansluitklem flexibele kabels (mm ²)	Max. 1,5	240 V Fluorescent lamps	-
Aanspanvermogen aansluitklem starre kabels (mm ²)	Max. 1,5	Load control	-
Context	Dry indoor places	Acoustic signalling element	Buzzer
IP- graad	IP20 (with plate fitted)	Standaard	2014/35/EU (LVD), 2014/30/EU (EMC), 2011/65/EU + 2015/863 (RoHS), EN 60669-2-1, EN 60669-1, EN IEC 63000

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with plate fitted)

STANDARDS/APPROVALS

