


Flush-mounting touch dimmer module. Two touch areas on the front for switching the connected load ON and OFF (short press) or for regulating the brightness (long press). The device must be completed with one of the ICE Touch plates available. Inside the package of the plates is a sheet of interchangeable icons to customize the control symbol. The device has N°3 DIP-switches, located on the back of the device, for feature configuration.

Omschrijving	Aanraakdimmer	Voeding	100 ÷ 240 V ac - 50/60 Hz
Aantal modules	1	Aantal ingangskanalen	2
Local control	Via 2 frontal touch areas (must be completed with ICE Touch plate)	Auxiliary input channel voltage	100 ÷ 240 V ac - 50/60 Hz
Opslagtemperatuur	-25 ÷ +70 °C	Aantal uitgangskanalen	1
Bedrijfstemperatuur	-5 ÷ +45 °C	Relative humidity (non-condensative)	Max 93%
240 V ac Incandescent-halogen lamps	4 ÷ 150 W	Front light signaling	Blauwe led
240 V ac LED lamps	4 ÷ 150W (max 5 lamps)	Aansluitklemmen voor bekabeling	Met schroef
Loads piloted from electronic transf. 240 V ac	4 ÷ 150 VA (240 V ac)	Aanspanvermogen aansluitklem flexibele kabels (mm ²)	Max. 1,5
240 V Fluorescent lamps	-	Aanspanvermogen aansluitklem starre kabels (mm ²)	Max. 1,5
Load control	Trailing edge	Context	Dry indoor places
Acoustic signalling element	Buzzer	IP-grad	IP20 (with plate fitted)
Standaard	2014/35/EU (LVD), 2014/30/EU (EMC), 2011/65/EU + 2015/863 (RoHS), EN 60669-2-1, EN 60669-1, EN IEC 63000		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with plate fitted)

STANDARDS/APPROVALS



