


Flush-mounting axial auxiliary module with one command. An axial push-buttons on the front; this product can be used in combination with the auxiliary wired inputs of the following devices of the Chorusmart range: connected commands, connected 1- channel On/Off actuator, connected movement sensors, EVO commands, or as a wired command for a connected 2-channel ZigBee interface. The module with 1 auxiliary axial command can also be used to directly command small resistive or weakly inductive loads such as ringers and buzzers (max. 10VA);. The device must be completed with one of the front buttons key available.

Omschrijving	1-channel auxiliary axial command	Voeding	100 ÷ 240 V ac - 50/60 Hz
Aantal modules	2	Aantal ingangs-kanalen	-
Local control	Via front push button (to complete with button key)	Auxiliary input channel voltage	-
Opslagtemperatuur	-25 ÷ +70 °C	N. of LED input channels	1
Bedrijfs-temperatuur	-5 ÷ +45 °C	LED input channels voltage	100 ÷ 240 V ac - 50/60 Hz
Relative humidity (non-condensative)	Max 93%	Aantal uitgangs-kanalen	1
Front light signaling	Blauwe led	Uitgang contacten	1A (AC1)
Aansluitklemmen voor bekabeling	Met schroef	240 V ac Incandescent-halogen lamps	-
Aanspanvermogen aansluitklem flexibele kabels (mm ²)	Max. 1,5	240 V ac LED lamps	-
Aanspanvermogen aansluitklem starre kabels (mm ²)	Max. 1,5	Loads piloted from electronic transf. 240 V ac	-
Context	Dry indoor places	240 V Fluorescent lamps	-
IP-graad	IP20 (with button key)	Load control	-
Standaard	2014/35/EU (LVD), 2011/65/EU + 2015/863 (RoHS), EN 60669-1, EN IEC 63000		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with button key)

STANDARDS/APPROVALS



