




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Kleur	Glossy white	Uitgang contacten	1 NO / NC 5A (AC1) 240 V ac
Voeding	100 ÷ 240 V ac - 50/60 Hz	Aantal modules	2
Radio connections	Zigbee (IEEE 802.15.4)	Standaard	2014/53/EU, 2011/65/EU + 2015/863, EN 60730-1, EN 60730-2-7, EN 60730-2-9, EN 301 489-1, EN 301 489-17, EN 300 328, EN IEC 63000
Bedrijfs-temperatuur	-5 ÷ +45 °C	Relative humidity (non-condensative)	Max 93%
Power output Zigbee	10 dBm	Aansluitklemmen voor bekabeling	Met schroef
Aanspanvermogen aansluitklem flexibele kabels (mm <sup>2</sup> )	Max. 1,5	Aanspanvermogen aansluitklem starre kabels (mm <sup>2</sup> )	Max. 1,5
Categorie	Thermostaat	IP-graad	IP20
Gemeten maten	Temperature, humidity	Functies	Heating and cooling control; algorithms for 2-way systems: two-point (On/Off) and proportional integral (PWM).
Type scherm	LCD		

## DIMENSIONAL



## TECHNICAL SYMBOLOGY

# IP

IP20

## STANDARDS/APPROVALS

