


Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

| | | | |
|---|--|---|---|
| Kleur | Glossy white | Uitgang contacten | 1 NO 16 A (AC1) 240 V ac |
| Voeding | 100 ÷ 240 V ac - 50/60 Hz | Aantal modules | 1 |
| Aantal uitgangskanalen | 1 | Radio connections | Zigbee (IEEE 802.15.4) |
| Bedrijfstemperatuur | -5 ÷ +45 °C | Relative humidity (non-condensative) | Max 93% |
| Power output Zigbee | 10 dBm | Aansluitklemmen voor bekabeling | Met schroef |
| Aanspanvermogen aansluitklem flexibele kabels (mm ²) | Max. 2,5 | Aanspanvermogen aansluitklem starre kabels (mm ²) | Max. 2,5 |
| Categorie | 1-channel actuator with energy meter | Aantal ingangskanalen | 1 (for local command replication or sending additional Zigbee commands) |
| Ingangspanning | Mains supply voltage | IP-grad | IP20 |
| 240 V ac Incandescent-halogen lamps | 1920 W | 240 V ac LED lamps | 200 W |
| Loads piloted from electronic transf. 240 V ac | 500 VA | LED colour | Blauw |
| Local control | Using front button | Power supply of EGO SMART plate | Ja |
| Zigbee control extension if installed in an EGO SMART plate (SHIFT function) Yes (1 Zigbee command) | | Gemeten maten | Active power, energy consumed |
| Functies | Timed load control, measures consumption, disconnection of load after exceeding threshold. | | |

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20

STANDARDS/APPROVALS



