




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Kleur	Satijnzwart	Uitgang contacten	1 NO 16 A (AC1) 240 V ac
Voeding	100 ÷ 240 V ac - 50/60 Hz	Aantal modules	1
Aantal uitgangskanalen	1	Radio connections	Zigbee (IEEE 802.15.4)
Bedrijfstemperatuur	-5 ÷ +45 °C	Relative humidity (non-condensative)	Max 93%
Power output Zigbee	10 dBm	Aansluitklemmen voor bekabeling	Met schroef
Aanspanvermogen aansluitklem flexibele kabels (mm ²)	Max. 2,5	Aanspanvermogen aansluitklem starre kabels (mm ²)	Max. 2,5
Categorie	1-channel actuator with energy meter	Aantal ingangskanalen	1 (for local command replication or sending additional Zigbee commands)
Ingangsspanning	Mains supply voltage	IP-grad	IP20
240 V ac Incandescent-halogen lamps	1920 W	240 V ac LED lamps	200 W
Loads piloted from electronic transf. 240 V ac	500 VA	LED colour	Blauw
Local control	Using front button	Power supply of EGO SMART plate	Ja
Zigbee control extension if installed in an EGO SMART plate (SHIFT function) Yes (1 Zigbee command)		Gemeten maten	Active power, energy consumed
Functies	Timed load control, measures consumption, disconnection of load after exceeding threshold.		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20

STANDARDS/APPROVALS



