



Wall-mounting thermostat to control heating/cooling and humidification/dehumidification systems and manage the temperature in manual mode or on 3 levels (comfort, pre-comfort, economy). Control algorithms for two-way systems: two points (ON/OFF), proportional integral (PWM). Includes 2 output contacts for heating, cooling or humidity control. Includes 1 input for external NTC temperature sensor (for room temperature measurement compensation or for underfloor heating protection). Equipped with a user interface with touch controls (capacitive) on technopolymer plate and backlit display. The thermostat has built-in proximity, temperature and humidity sensors and a Wi-Fi interface for setting parameters and programming temperature profiles (timed thermostat function) locally or remotely via specific apps (smartphone and tablet). The device can be used:

- as an independent intelligent thermostat (in a stand-alone way), i.e. without the need for a Smart Home system, in this case the configuration and control of the device takes place via the "ThermoICE 2.0" APP;
- integrated into the Gewiss "Connected Smart Home" system, in this case the device can interoperate with all the other devices of the "Connected Smart Home" system and is configured and controlled together with all the other functions of the system via the "Home Gateway" APP.

all the other devices of the "Connected Smart Home" system and is configured and controlled together with all the other functions of the system via the "Home Gateway" APP.

Wall-mounting installation with wall-plugs or on 3-modules rectangular boxes (centre distance 83.5 mm). Equipped with front plate. Plate material: technopolymer.

Categorie	Thermo ICE-thermostaten	Comunicatie	Wifi
Kleur	Natural beige	Material	Front plate in technopolymer
Installatie	Wall mount	Voeding	110-230V ac - 50/60Hz
Current absorbed by power supply	< 3 W (in stand-by < 1 W)	Interfaces	Wi-Fi 2.4GHz IEEE 802.11 b/g/n
Gemeten maten	Temperature, humidity, one additional input for external NTC temperature sensor	Aantal uitgangs-kanalen	2 NO potential free
Uitgang contacten	Max switching current at 250Vac: 6A ($\cos\phi = 1$); 1,5A ($\cos\phi = 0,6$)	Aantal ingangs-kanalen	1 for external NTC sensor (type: NTC 10K, es. GW 10 800)
Ingangs-spanning	-	Aansluitklemmen voor bekabeling	Met Schroef
Aanspanvermogen aansluitklem flexibele kabels (mm^2)	Max 1,5 mm^2	Aanspanvermogen aansluitklem starre kabels (mm^2)	Max 1,5 mm^2
Bedrijfs-temperatuur	-5 + +45 °C	Relative humidity (non-condensative)	Max 93%
Opslagtemperatuur	-25 + +70 °C	Afmetingen LxHxD (mm)	123,2x95,2x20,6
IP-graad	IP20	Standaard	Directive RoHS 2011/65/EU + 2015/863 Directive RED 2014/53/EU EN 60730-2-9; EN 60730-2-7; EN 60730-1; EN 301 489-1; EN 301 489-17; EN 300 328; EN IEC 63000

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20

STANDARDS/APPROVALS

UK CA CE

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 17/07/2024

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice