


Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Uitgang contacten	1 NO / NC 2 A (AC1) 240 V ac	Voeding	100 ÷ 240 V ac - 50/60 Hz
Aantal modules	1	Aantal uitgangskanalen	1
Radio connections	Zigbee (IEEE 802.15.4)	Standaard	2014/53/EU, 2011/65/EU + 2015/863, EN 60669-2-1, EN 60669-1, EN 301 489-1, EN 301 489-17, EN 300 328, EN IEC 63000
Bedrijfstemperatuur	-5 ÷ +45 °C	Relative humidity (non-condensative)	Max 93%
Power output Zigbee	10 dBm	Max. vermogenverspreiding (W)	2,6
Aansluitklemmen voor bekabeling	Met schroef	Aanspanvermogen aansluitklem flexibele kabels (mm²)	Max. 1,5
Aanspanvermogen aansluitklem starre kabels (mm²)	Max. 1,5	Categorie	Axial 2-way switch connected
Aantal ingangskanalen	2 (for local command replication or sending additional Zigbee commands)	Ingangsspanning	Mains supply voltage
IP-graad	IP20 (with button key)	240 V ac Incandescent-halogen lamps	4-500 W
240 V ac LED lamps	4-100 W	Loads piloted from electronic transf. 240 V ac	4-250 VA
LED colour	Blauw	Local control	Via front push button (to complete with button key)
Power supply of EGO SMART plate	Ja	Zigbee control extension if installed in an EGO SMART plate (SHIFT function)	Yes (1 Zigbee command)
Functies	Timed load control, indicative measurement of active power and consumed energy		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with button key)

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 17/07/2024

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice