




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Uitgang contacten	1 NO / NC 2 A (AC1) 240 V ac	Voeding	100 ÷ 240 V ac - 50/60 Hz
Aantal kanalen	0	Aantal modules	2
Aantal uitgangskanalen	1	Radio connections	Zigbee (IEEE 802.15.4)
Standaard	2014/53/EU, 2011/65/EU + 2015/863, EN 60669-2-1, EN 60669-1, EN 301 489-1, EN 301 489-17, EN 300 328, EN IEC 63000	Bedrijfstemperatuur	-5 ÷ +45 °C
Relative humidity (non-condensative)	Max 93%	Power output Zigbee	10 dBm
Max. vermogensverspreiding (W)	2,6	Aansluitklemmen voor bekabeling	Met schroef
Aanspanvermogen aansluitklem flexibele kabels (mm ²)	Max. 1,5	Aanspanvermogen aansluitklem starre kabels (mm ²)	Max. 1,5
Categorie	Axial 2-way switch connected	Aantal ingangskanalen	2 (for local command replication or sending additional Zigbee commands)
Ingangsspanning	Mains supply voltage	IP-graad	IP20 (with button key)
240 V ac Incandescent-halogen lamps	4-500 W	240 V ac LED lamps	4-100 W
Loads piloted from electronic transf. 240 V ac	4-250 VA	LED colour	Blauw
Local control	Via front push button (to complete with button key)	Power supply of EGO SMART plate	Ja
Zigbee control extension if installed in an EGO SMART plate (SHIFT function)	Yes (1 Zigbee command)	Functies	Timed load control, indicative measurement of active power and consumed energy

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with button key)

STANDARDS/APPROVALS



