




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Uitgang contacten	2,3 A 240 V ac (according to IEC 60669-2-1)	Voeding	100 ± 240 V ac - 50/60 Hz
Aantal modules	2	Aantal uitgangskanalen	1
Radio connections	Zigbee (IEEE 802.15.4)	Standaard	2014/53/EU, 2011/65/EU + 2015/863, EN 60669-2-1, EN 60669-1, EN 301 489-1, EN 301 489-17, EN 300 328, EN IEC 63000
Bedrijfstemperatuur	-5 + +45 °C	Relative humidity (non-condensative)	Max 93%
Power output Zigbee	10 dBm	Max. vermogenverspreiding (W)	2
Aansluitklemmen voor bekabeling	Met schroef	Aanspanvermogen aansluitklem flexibele kabels (mm²)	Max. 1,5
Aanspanvermogen aansluitklem starre kabels (mm²)	Max. 1,5	Categorie	Axial roller shutter command connected
Aantal ingangskanalen	2 (for local command replication or sending additional Zigbee commands)	Ingangsspanning	Mains supply voltage
IP-graad	IP20 (with button key)	LED colour	Blauw
Local control	Via 2 front push buttons (to complete with button key)	Power supply of EGO SMART plate	Ja
Zigbee control extension if installed in an EGO SMART plate (SHIFT function)	Yes (2 Zigbee command activated with front push buttons)		

## DIMENSIONAL



## TECHNICAL SYMBOLOGY

### IP

IP20 (with button key)

## STANDARDS/APPROVALS



