


Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Voeding	100 ÷ 240 V ac - 50/60 Hz	Aantal kanalen	2
Aantal modules	2	Radio connections	Zigbee (IEEE 802.15.4)
Standaard	-	Bedrijfs-temperatuur	-5 ÷ +45 °C
Relative humidity (non-condensative)	Max 93%	Power output Zigbee	10 dBm
Aansluitklemmen voor bekabeling	Met schroef	Aanspanvermogen aansluitklem flexibele kabels (mm ²)	Max. 1,5
Aanspanvermogen aansluitklem starre kabels (mm ²)	Max. 1,5	Categorie	2-channel push-button control panel
Aantal ingangskanalen	2 (for local command replication or sending additional Zigbee commands)	Ingangsspanning	Mains supply voltage
IP-graad	IP20 (with button key)	LED colour	Blauw
Local control	Via 2 front push buttons (to complete with button key)	Power supply of EGO SMART plate	Ja
Zigbee control extension if installed in an EGO SMART plate (SHIFT function)	Yes (2 Zigbee command activated with front push buttons)		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with button key)

STANDARDS/APPROVALS

