




Complete system for the connection and distribution of LAN networks in residential and tertiary sector environments.

The range includes fibre optic solutions, wall panels, floor cabinets and copper wiring products.

The Data Center series provides all the products necessary to create a multi-service fibre optic infrastructure for residential buildings, in full compliance with all the indications dictated by the new IEC Guide 306-2 and Law 164/14.

Categorie	Optical connector	Cable colour	Wit
No. optical fibers	1	Lengthe	20 m
Ø sheath	2 mm	For connectors	SC/APC - SC/APC
Classificering	G.657.A2 / B6_a2 Bend Insensitive	Ø core	9 µm
Ø cladding	125 µm	Strength member	Kevlar
Outer jacket	LSZH	Cable	Loose - OS2
Tension	60 N	Crush	100 N/10cm
Minimum bend radius (Dynamic)	20x cable diameter	Minimum bend radius (Static)	10x cable diameter
Max attenuation (@1310 nm / @1550 nm)	0.35 / 0.2 dB/Km	Bedrijfs-temperatuur	From -20°C to +60°C

### DIMENSIONAL



### STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 28/06/2022

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice