



Wirelessly connected device with Zigbee protocol from the ChoruSmart system. It can be used with Home Gateway for "CONNECTED SMART HOME" solutions and with Smart Gateway for "HOME AND BUILDING PRO" solutions. Ideal for residential and small commercial offices, new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node within the network ensures reachability across all devices (mesh network). This device can also be used without Home Gateway and Smart Gateway (manual configuration with dip-switch or via IoT Configurator), in which case supervision via the app is not possible.

Categorie	Slimme stekker	Kleur	Wit
Communicatieprotocol	Zigbee (IEEE 802.15.4)	Max. stroom meegeleverd	10 A
Output power	8 dBm	Max. vermogen-verspreiding (W)	2 W
Type stekker	2P+E - 10 A	Contactdoos type	2P+E - 10 A
Standaard	2014/53/EU	IP-graad	IP40
Bedrijfs-temperatuur	0 ÷ +40 °C	Opslagtemperatuur	-20 ÷ +80 °C
Relative humidity (non-condensative)	Max 93%	Afmetingen ØxH (mm)	41x45 mm
Electrocod	051A		

## DIMENSIONAL

## TECHNICAL SYMBOLOGY

**IP**

IP40

## STANDARDS/APPROVALS

