




The System modular devices allow the creation of infinite combinations of devices and plates, through a complete range that covers all design, functional and installation needs. Colours and finishes: satin black, elegant and classy. Ideal for flush-mounted solutions (for rectangular or square boxes), surface-mounted solutions and special applications. The range includes control units, socket-outlets, breakers, indicators, connectors and devices for the control, safety and comfort of your home

Categorie	Socket-Outlet	Omschrijving	2P+E - 10 A
Kleur	Zwart	Spanning	250 V AC
Aard-gat	-	Standaard	Engels
Eigenschappen	Met schroef	Voor stekkerpennen	Ø 4 mm
Type	P11	Standaard	CEI 23-50
Bestendigheid bij testspanning	2000 V bij 50 Hz gedurende 1 minuut	Verlengd bedrijf (aantal positiewijzigingen)	10.000 bij In 250 V AC cosφ=0,8
Thermospanning met kogel	125 °C	Gloedraadproef	850 °C
Klemgreep op kabeltractie	> 50 N	Aanspanvermogen aansluitklem flexibele kabels (mm ²)	min. 0,75 - max. 2x4
Aanspanvermogen aansluitklem starre kabels (mm ²)	min. 0,5 - max. 2x2,5	Aantal SYSTEM-modules	1
Materiaal	Technopolymeer	Electrocod	0131

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

