



The System modular devices allow the creation of infinite combinations of devices and plates, through a complete range that covers all design, functional and installation needs. Colours and finishes: satin black, elegant and classy. Ideal for flush-mounted solutions (for rectangular or square boxes), surface-mounted solutions and special applications. The range includes control units, socket-outlets, breakers, indicators, connectors and devices for the control, safety and comfort of your home

| | | | |
|---|-------------------------------------|--|---------------------------------|
| Categorie | Socket-Outlet | Omschrijving | 2P+E - 16 A dubbele ampérage |
| Kleur | Zwart | Spanning | 250 V AC |
| Aard-gat | - | Standaard | Engels |
| Eigenschappen | Met schroef | Voor stekkerpennen | Ø 4 / 5 mm |
| Type | P17-11 | Standaard | CEI 23-50 |
| Bestendigheid bij testspanning | 2000 V bij 50 Hz gedurende 1 minuut | Verlengd bedrijf (aantal positiewijzigingen) | 10.000 bij In 250 V AC cosφ=0,8 |
| Thermospanning met kogel | 125 °C | Gloedraadproef | 850 °C |
| Klemgreep op kabeltractie | > 50 N | Aanspanvermogen aansluitklem flexibele kabels (mm ²) | min. 0,75 - max. 2x4 |
| Aanspanvermogen aansluitklem starre kabels (mm ²) | min. 0,5 - max. 2x2,5 | Aantal SYSTEM-modules | 1 |
| Materiaal | Technopolymeer | Electrocod | 0131 |

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

