



The System modular devices make it possible to create infinite combination between devices and plates, thanks to a complete range that is able to satisfy all design, functional and installation requirements. Colour and finiture: glossy white, bright and versatile
Ideal for flush-mounting solutions (for rectangular or square boxes), surface-mounting solutions, and for special applications. The range includes commands, socket- outlets, protection, indicators, connectors and devices for the control, safety and comfort of your home.

Categorie	Socket-Outlet	Omschrijving	2P+E - 16 A dubbele ampèrage
Kleur	Wit	Spanning	250 V AC
Aard-gat	-	Standaard	Engels
Eigenschappen	Met sluiting voor kinderbeveiliging	Voor stekkerpennen	Ø 4 / 5 mm
Aansluitklemmen voor bekabeling	Met schroef	Type	P17-11
Standaard	CEI 23-50	Bestendigheid bij testspanning	2000 V bij 50 Hz gedurende 1 minuut
Verlengd bedrijf (aantal positiewijzigingen)	10.000 bij In 250 V AC $\cos\phi=0,8$	Thermospanning met kogel	125 °C
Gloeidraadproef	850 °C	Klemgreep op kabeltractie	> 50 N
Aanspanvermogen aansluitklem flexibele kabels (mm ²)	min. 0,75 - max. 2x4	Aanspanvermogen aansluitklem starre kabels (mm ²)	min. 0,5 - max. 2x2,5
Aantal SYSTEM-modules	1	Materiaal	Technopolymeer
Electrocod	0131		

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

