


The System modular devices make it possible to create infinite combination between devices and plates, thanks to a complete range that is able to satisfy all design, functional and installation requirements. The range includes commands, socket- outlets, protection, indicators, connectors and devices for the control, safety and comfort of your home.

Categorie	Socket-Outlet	Omschrijving	2P+E - 16 A
Group	Voor toegewezen leidingen	Kleur	Oranje
Spanning	250 V AC	Aard-gat	-
Standaard	Duitse norm	Eigenschappen	Met sluiting voor kinderbeveiliging
Voor stekkerpennen	Ø 4,8 mm	Aansluitklemmen voor bekabeling	Met schroef
Type	-	Standaard	IEC 60884-1; DIN VDE 0620-1
Bestendigheid bij testspanning	2000 V bij 50 Hz gedurende 1 minuut	Isolatiweerstand	> 5 MOhm
Verlengd bedrijf (aantal positiewijzigingen)	10.000 bij In 250 V AC cosφ=0,8	Thermospanning met kogel	125 °C
Gloeidraadproef	850 °C	Klemgreep op kabeltractie	> 50 N
Aanspanvermogen aansluitklem flexibele kabels (mm ²)	min. 0,75 - max. 2x4	Aanspanvermogen aansluitklem starre kabels (mm ²)	min. 0,5 - max. 2x2,5
Aantal SYSTEM-modules	2	Materiaal	Technopolymeer
Electrocod	0131		

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

