



The System modular devices make it possible to create infinite combination between devices and plates, thanks to a complete range that is able to satisfy all design, functional and installation requirements. Colour and finiture: glossy white, bright and versatile
Ideal for flush-mounting solutions (for rectangular or square boxes), surface-mounting solutions, and for special applications. The range includes commands, socket- outlets, protection, indicators, connectors and devices for the control, safety and comfort of your home.

Categorie	Voeding	Omschrijving	2x2P+E 16 A dubbele amp.
Kleur	Wit	Spanning	250 V AC
Aard-gat	-	Standaard	Engels
Eigenschappen	Met sluiting voor kinderbeveiliging	Voor stekkerpennen	Ø 4 / 5 mm
Aansluitklemmen voor bekabeling	Met schroef	Type	P17-11
Bestendigheid bij testspanning	2000 V bij 50 Hz gedurende 1 minuut	Verlengd bedrijf (aantal positiewijzigingen)	10.000 bij In 250 V AC cosφ=0,8
Thermospanning met kogel	125 °C	Gloedraadproef	850 °C
Klemgreep op kabeltractie	> 50 N	Aanspanvermogen aansluitklem flexibele kabels (mm ²)	min. 0,75 - max. 2x4
Aanspanvermogen aansluitklem starre kabels (mm ²)	min. 0,5 - max. 2x2,5	Aantal SYSTEM-modules	2
Materiaal	Technopolymeer	Electrocod	0131

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

