


SMART [4]




Smart [4] is a series of LED indoor appliances suitable for the lighting of industries and sports facilities. It is available in HE (High Efficiency), HLO (High Lumen Output) and integrated DALI Emergency. Three different sizes available: 1M, 2M and 4M. The body is made of "Halogen-free" nylon loaded with grey glass fibre (RAL7035) with vent and anti-condensation device in aluminium alloy EN AB 44300. It is equipped with a dual optical system that includes a metallic reflector with ARRAY optics and a metallic reflector with UV stabilized PMMA lenses, with high efficiency, which allow a wide variety of light distributions 30°, 60°, 90°, Asymmetric and Elliptical. The version with through wiring has pre-wired mechanical and electrical connection components. Suspension, wall and projection appliances can be installed. It is available with three types of Colour Temperature (3000K / 4000K / 5700K), Color Rendering Index CRI>80 and two power supply options (ON/OFF or DALI).

GENERAL INFORMATION		OPTIC AND ILLUMINATING FEATURES	
Context	Lighting for industries and large sports facilities	Optiek	Array
Luminaire	LED Industrial Reflector	Unified Glare Rating	UGR ≤ 25
Toepassing	Intern	Lumen output (lm)	29200 (900 Em.)
Unique digital code (Datamatrix)	Datamatrix	Efficacy (lm/W)	154
Kleur	Grijs RAL 7035	Kleur temperatuur	3000 K
Type lichtbron	LED	Colour Rendering Index	CRI>80
System power	189 W (+5W Emerg.)	Standard Deviation Colour Matching	SDCM = 3
LED Lifetime	L90B10 (Tq+25°C) = 100.000 h - L90B10 (Tq+50°C) = 50.000 h	Photobiological Risk Class	RG0
Gewicht (kg)	15	Standaard	EN 60598-2-22 ; EN 60598-1 ; EN 60598-2-24
Garantie	5 jaar	ELETRICAL AND LIGHTING FEATURES	
Opslagtemperatuur	-40 +70 °C	Voedingsspanning	220 - 240 V
Operating temperature	0 ÷ +40 °C	Nominale frequentie (Hz)	50/60 Hz
MATERIALS		Driver	Included
Body	PA6 "Halogen Free" loaded fibreglass	Type plaat	Tempered glass Thickness 4mm
Overvoltage protection	DM 6 kV / CM 10 kV	Optic	Metallized polycarbonate reflector
Control System	1 x DALI DT6 + 1 x DALI DT1 (Emerg. 3h)	Gasket	anti-aging silicone
INSTALLATION AND MAINTENANCE		STANDARDS AND APPROVALS	
Mounting and installation	Ceiling light - Suspension	Locking Hook	-
Tilt	-	External screw	Roestvrij staal
Wiring	With GW connect watertight connector	Colour	Grijs RAL 7035
Bevestiging	-	STANDARDS AND APPROVALS	
Light source replaceability	By professional	Classificering	-
Controlgear replaceability	By professional	Toestel met verlaagde oppervlaktetemperatuur	Ja
Driver Box	Ingebouwd	DIN 18032-3-certificering	Available (under certain installation conditions)
Maximum surface exposed to the wind	0,390 m ²	IPEA	-
		Isolatie-klasse	I
		IP-graad	IP65
		Stootbestendigheid	IK08
		Glow Wire Test	850 °C

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



SMART [4]

TECHNICAL SYMBOLOGY



0,390 m²



IP
IP65

IK
IK08

GWT
850 °C

STANDARDS/APPROVALS

