

Smart [PRO] 2.0


Geïntegreerde oplossing voor professionele sportaccomodaties en grote buitenruimtes




SMART [PRO] 2.0 is a medium power outdoor and indoor LED projector, suitable for lighting sports areas and facilities. It can be installed on the wall, ceiling or ground thanks to the polyester powder coated galvanised steel bracket, with trivalent passivation, equipped with adjustable goniometric scale and supplied in kit. The body is produced in aluminium die casting EN AB 46100, with integrated passive heat sink, powder coated polyester with trivalent passivation. Metal core PCB with CSP LED. Reflector made of metallic HT PC or anodised and polished aluminium. Hardened front glass with 4mm thickness, anti-ageing silicone seals and A2 stainless steel exterior screws. Plastic venting and anti-condensation device. Electrical connection via IP68 connector for 1.5mm² cables. Insulation class 1. Driver integrated in options 1-10 V or DALI. Available with nine different types of optics, three types of Colour Temperature (3,000K/4,000K/5,700K) and two different types of Chromatic Yield Index (CRI>70, CRI>80). Designed to withstand surges up to 5KV (RCCB mode) and 10KV (common mode), temperature variations from -30°C to +50°C, water and dust penetration up to IP66 protection and impacts up to IK08.

GENERAL INFORMATION		- OPTIC AND ILLUMINATING FEATURES	
Context	Sport, Big Areas	Optiek	C1 - Circular 30°
Luminaire	LED luminaire with small, mid and high lumen power	Unified Glare Rating	G*6 - ULOR = 0
Toepassing	Binnenshuis / buitenshuis	Lumen-vermogen (lm)	37300
Unique digital code (Datamatrix)	Currently not present	Efficacy (lm/W)	113
Kleur	Grafietgrijs	Kleur temperatuur	3000 K
Type lichtbron	LED	Colour Rendering Index	CRI>70
System vermogen	330 W	Standard Deviation Colour Matching	SDCM = 5
LED Lifetime	L90B10(Tq25°C)=40.000h; L80B10(Tq25°C)=90.000h	Photobiological Risk Class	-
Gewicht (kg)	13	Standaard	EN60598-1; EN60598-2-5; IEC 62778; IEC 62471; EN13201
Garantie	5 jaar	ELETRICAL AND LIGHTING FEATURES	
Opslagtemperatuur	-	Voedings-spanning	220 - 240 V
Operating temperature	-30°C + +50 °C	Nominale frequentie (Hz)	50 / 60
MATERIALS		- Driver	
Body	Gietaluminium	Driver failure rate	Included F10 = 80.000h Tq25°C
Type plaat	Flat tempered glass 4mm	Overvoltage protection	DM 5KV / CM 10KV
Optic	Polished quartz and metallized PC HT reflector	Control System	Standalone - 1/10 V
Gasket	Anti-ageing silicone	INSTALLATION AND MAINTENANCE	
Locking Hook	Hexagonal metric screws	Mounting and installation	High-mast lighting - Wall mounting - Ground mouting
External screw	Stainless steel	Tilt	Rotation on bracket with integrated goniometer
Colour	Polyester powder coated	Wiring	Watertight connector
STANDARDS AND APPROVALS		- Bevestiging	
Classificering	-	Light souce replaceability	By professional
Toestel met verlaagde oppervlaktetemperatuur	Nee	Controlgear replaceability	By professional
DIN 18032-3-certificering	Available	Driver Box	Ingebouwd
IPEA	-	Maximum surface exposed to the wind	0,170 m2
Isolatie-klasse	I		-
IP-graad	IP66		-
Stoot-bestendigheid	IK08		-
Glow Wire Test	-		-

DIMENSIONAL




PHOTOMETRIC DISTRIBUTION



Data, measures, designs and pictures are for information purpose only, last update 18/07/2024. They can be changed at any moment, therefore it is always recommended to read the last updated version published on the website www.gewiss.com. Lumen output and system power are subject to a tolerance of +/- 10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C. Terms of warranty at <https://www.gewiss.com/it/en/company/landingpage/led-warranty>. - 1 of 2

Smart [PRO] 2.0

Geïntegreerde oplossing voor professionele sportaccomodaties en grote buitenruimtes



TECHNICAL SYMBOLOGY



IP
IP66

IK
IK08

GWT
-

STANDARDS/APPROVALS

