



Smart [PRO]e




SMART [PRO]e 2M is a medium-power outdoor and indoor LED floodlight, ideal for lighting small to medium-sized areas and sports facilities. It can be installed on the wall, ceiling or ground thanks to the galvanised steel bracket which is powder coated in polyester with trivalent passivation and equipped with an adjustable goniometric scale and supplied in kit form. The main body is made in die cast aluminium EN AB 46100, with an integrated passive heat sink, and powder coated polyester frame with trivalent passivation. COB LED technology for high efficacy. Reflector made of metallised PC-HT or anodised and polished aluminium. 4mm thick toughened front glass, silkscreen printed for symmetrical versions or with anti-reflective nanocoating for asymmetrical versions. Anti-ageing silicone gaskets and A2 stainless steel exterior screws. Plastic venting and anti-condensation device. Electrical connection via 5x1mm² H07RN-F cable. Insulation Class 1. Built-in 1-10V dimmable driver. Available with five different types of optics, three types of Correlated Colour Temperature (3000K/4000K/5700K) and two different types of Colour Rendering Index (CRI70, CRI80). Designed to withstand surges up to 6KV (differential mode) and 10KV (common mode), temperature variations from -30°C to +50°C, water and dust penetration up to IP66, and impact up to IK08.

| GENERAL INFORMATION | | OPTIC AND ILLUMINATING FEATURES | |
|--|--|-------------------------------------|---|
| Context | Floodlighting and small- to medium-size sports facilities | Optiek | ALW - Asymmetrical Medium |
| Luminaire | LED luminaire with mid lumen power | Unified Glare Rating | G*6 - ULOR = 0% |
| Toepassing | Binnenshuis / buitenshuis | Lumen-vermogen (lm) | 40800 |
| Unique digital code (Datamatrix) | Currently not present | Efficacy (lm/W) | 136 |
| Kleur | Grafietgrijs | Kleur temperatuur | 4000 K |
| Type lichtbron | LED | Colour Rendering Index | CRI>70 |
| System vermogen | 300 W | Standard Deviation Colour Matching | SDCM = 3 |
| LED Lifetime | L90B10 (Tq+25°C) = 100000h; L80B10 (Tq+25°C) > 150000h | Photobiological Risk Class | RG1 |
| Gewicht (kg) | 13 | Standaard | EN60598-1; EN60598-2-5; IEC62778; EN13201 |
| Garantie | 5 jaar | ELETRICAL AND LIGHTING FEATURES | |
| Opslagtemperatuur | - | Voedings-spanning | 220 - 240 V |
| Operating temperature | -30°C ÷ +50 °C | Nominale frequentie (Hz) | 50 / 60 |
| MATERIALS | | Driver | Included |
| Body | Gietaluminium - | Driver failure rate | F10 = 100.000h Tq25°C |
| Type plaat | Anti-reflective super-transparent 4 mm thick surface glass | Overvoltage protection | DM 6 kV / CM 10 kV |
| Optic | Polished anodised aluminium reflector with 99.99% pure aluminium | Control System | Standalone - 1/10 V |
| Gasket | Anti-ageing silicone | INSTALLATION AND MAINTENANCE | |
| Locking Hook | - | Mounting and installation | High-mast lighting - Wall mounting - Ground mouting |
| External screw | Stainless steel | Tilt | Rotation on bracket with integrated goniometer |
| Colour | Polyester powder coated with epoxy base coat | Wiring | With H07RN-F multi-pole cable |
| STANDARDS AND APPROVALS | | - | Bevestiging |
| Classificering | - | Light souce replaceability | By professional |
| Toestel met verlaagde oppervlaktetemperatuur | - | Controlgear replaceability | - |
| DIN 18032-3-certificering | Conform | Driver Box | Ingebouwd |
| IPEA | - | Maximum surface exposed to the wind | 0,170 m2 |
| Isolatie-klasse | I | - | - |
| IP-graad | IP66 | - | - |
| Stootbestendigheid | IK08 | - | - |

DIMENSIONAL




PHOTOMETRIC DISTRIBUTION



Data, measures, designs and pictures are for information purpose only, last update 01/07/2024. They can be changed at any moment, therefore it is always recommended to read the last updated version published on the website www.gewiss.com. Lumen output and system power are subject to a tolerance of +/- 10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C. Terms of warranty at <https://www.gewiss.com/it/en/company/landingpage/led-warranty>. - 1 of 2

Smart [PRO]e



TECHNICAL SYMBOLOGY



IP
IP66

IK
IK08

STANDARDS/APPROVALS

