




Omschrijving Interruttore automatico scatolato
 Code MSX 160
 Aantal polen 3P
 Nominale stroom 160 A
 Afschakelspoel Elettromeccanico

ELECTRICAL CHARACTERISTICS

MECHANICAL CHARACTERISTICS

Standaard	IEC/EN 60947-2	Uitvoering	Fisso - Rimovibile
Gebruik categorie	A	DIN rail mounting	SI, tramite accessorio
Nominale frequentie (Hz)	50 / 60	Accessoriabile con comando motore	SI
Rated operating voltage (Ue)	690 Vac - 250 Vdc	Compatible interlock	Lever – Cable
Nominale stoot-houdspanning (Uimp)	8 kV	Terminals supplied	Front FC
Overspannings-categorie	IV	Montage-positie	Elke
Isolatiespanning (Ui)	800 V	Upline/downline power supply	SI
Thermal regulation	0,63 - 0,8 - 1 x In	Electrical life (415Vac)	20.000 cycles
Magnetic regulation	6 - 8 - 10 - 13 x In	Mechanical life	30.000 cycles
Neutral protection	-	Bedrijfstemperatuur	-5°C +65°C
Total power loss	36.09 W	Opslagtemperatuur	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Gewicht (kg)	1.5
Rated short-time withstand current for 0,3s (Icw)	-	Width	105 mm
I _{dn} regulation	-	Hoogte	165 mm
DT regulation	-	Diepte	68 mm
SERVICE BREAKING CAPACITY (ICU)	-	RATED BREAKING CAPACITY (ICS)	-
220/240Vac	65 kA	220/240Vac	65 kA
400/415Vac	36 kA	400/415Vac	36 kA
440Vac	25 kA	440Vac	25 kA
525Vac	25 kA	525Vac	25 kA
690Vac	7,5 kA	690Vac	7,5 kA
250Vdc	40 kA	250Vdc	40 kA

DIMENSIONAL



STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 01/07/2024

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice