



System - 27 Combi

GEWISS

SYSTEM is the **all-Italian** modular domestic range from GEWISS. The whole range is **practical and robust, highly versatile**, and ideal for any flush or surface-mounting installations thanks to its full integration with the 27 COMBI system of modular enclosures.

The exclusive advantages of the System range




Wide design choice

System offers 14 colours and 2 different plate shapes, with modern (Mira) or classic (Top System) lines, a glossy finish and a capacity from 1 to 12 (6+6) gang. Ideal for both rectangular and square boxes. Also available in an IP55 watertight version.



High performance

The command devices are available in 16AX versions with a nominal current of 16A, also suitable for heavy-duty loads. These versions are designed for the safe control of inductive/capacitive load management over time.



A complete range

The System range includes commands, energy socket-outlets, TV-SAT socket-outlets, data socket-outlets, USB power supply units, protection, signalling, technical alarms, comfort controls (dimmers) and temperature adjustment (fan-coils).






















Integration with the 27 Combi range

The domestic range devices ensure full integration with all the enclosures of the 27 COMBI range, which offers a huge choice of protected enclosures (IP40) and watertight enclosures (IP55 and IP65) for both indoors and outdoors, for use even in extreme weather conditions.












Example of plates and modular devices

Supports, plates and IP55 plates				GW 22 601 - 1 gang GW 22 602 - 2 gang GW 22 603 - 3 gang GW 22 604 - 4 gang GW 22 606 - 6 gang GW 22 607 - 4+4 gang GW 22 608 - 6+6 gang		GW 22 101 - 1 gang GW 22 102 - 2 gang GW 22 103 - 3 gang GW 22 104 - 4 gang GW 22 106 - 6 gang GW 22 107 - 4+4 gang GW 22 108 - 6+6 gang		
	<p>GW 24 262 (screwed) - 2 gang</p>	<p>GW 24 201 (screwed) - 3 gang</p>	<p>Top System - titanium</p>		<p>Virna - cloud white</p>		<p>GW 22 451 3 gang - IP55 cloud white</p>	
USB power supply and energy socket-outlets					One-way switches and push-buttons			
	<p>GW 20 361 USB twin power supply</p>	<p>GW 20 212 2P+E -15A 250/125V AC</p>	<p>GW 20 265 2P+ E -16A -250V AC</p>	<p>GW 20 297 2P+ E -16A -250V AC</p>		<p>GW 20 572 1M-1P-16 AX Illuminated one-way switch 230V AC</p>	<p>GW 20 510 1M-1P-NO-10A Push-button</p>	<p>GW 20 521 1M-1P-NO+NO-10A Push-button with interlock</p>
Telephony, data and TV					Comfort			
	<p>TV/SAT socket-outlet F female</p>	<p>RJ45 socket-outlet - UTP</p>	<p>GW 20 391 - 0 dB</p>	<p>GW 20 392 - 5 dB</p>		<p>GW 20 393 - 14 dB</p>	<p>Dimmers</p>	<p>GW 20 853 Thermostat for fan-coil 230V AC -50/60 Hz</p>

Discover the complete System range at www.gewiss.com

Example of a configuration available from the catalogue

	+		=	
<p>GW 27 041</p>		<p>GW 20 571</p>		<p>GW 27 831</p>
	+		=	
<p>GW 27 002</p>		<p>GW 20 246</p>		<p>GW 27 812</p>
	+		=	
<p>GW 27 111</p>		<p>GW 74 361</p>		<p>GW 27 202</p>

Example of a custom configuration

	+		=			
<p>GW 27 042</p>		<p>GW 20 589</p>				
	+		+		=	
<p>GW 27 003</p>		<p>GW 20 503</p>		<p>GW 20 246</p>		
	+		+		=	
<p>GW 27 102</p>		<p>GW 74 301</p>		<p>GW 74 367</p>		