

Product Data Sheet **GW16703TBN**

CHORUSMART - Domestic range




Watertight plates IP55 ChoruSmart range for round/square (axles distance 60mm) and rectangular (3 and 4 modules) flush mounting boxes. Watertight plates equipped with support and long screws, for the installation of Chorusmart range devices. Ergonomic membrane, maximum opening angle lid 160° facilitated by a comfortable handle. IP55 degree guaranteed with closed lid and watertight plate mounted on smooth and waterproof walls, without grooves

Catagon	ChoruSmart series	Turne	Italian standard plates
Category	ChoruSmant series	Туре	Italian standard plates
Group	Watertight plates	Description	3 modules
Colour Plate	White	Finishing	Glossy
Material	Technopolymer	IP degree	IP55 (with closed lid)
Lid	With membrane	Membrane color	Transparent
For flush mounting box	Rectangular 3 modules	Fixing	2 screws (included)
Type of screw	6/32 x 30mm	Screw material	Galvanised steel
Included support	GW16803	Gasket	Vulcanized expanded rubber
Glow Wire Test	650 °C	Thermo-pressure with ball	70 °C
Standard	EN 60669-1	Operating temperature	-25 +60 °C
UV resistance	Yes (ISO 4892-2)	Maximum opening angle lid	160°
Electrocod	0110		



33



TECHNICAL SYMBOLOGY


IP

IP55 (with closed lid)



STANDARDS/APPROVALS

UK CE



160°



www.gewiss.com sat@gewiss.com Last update 22/11/2024 Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice