



Description Manual transfer switch disconnecter with three positions

Code MSS 125

No. of poles 4P

Rated current 100 A

ELECTRICAL CHARACTERISTICS

Standard	EN 60947-3
AC Rated operational voltage (Ue)	400V
DC Rated operational voltage (Ue)	-
AC Maximum operational voltage (Ue max)	690 V
DC Maximum operational voltage (Ue max)	220 V
Rated insulation voltage (Ui)	800 V
Rated impulse withstand voltage (Uimp)	8 kV
Rated short-time withstand current for 1s (Icw)	2,5 kA
Rated short-circuit current making capacity (Icm)	12 kA
Conditional short-circuit current with fuse (Icc)	100 kA (gG 100A)
Power dissipation per pole	3,1 W
AC RATED OPERATIONAL CURRENT (Ie)	
AC-20A / AC-20B (690V AC)	100 A / 100 A
AC-21A / AC-21B (400V AC)	100 A / 100 A
AC-21A / AC-21B (500V AC)	-
AC-21A / AC-21B (690V AC)	80 A / 80 A
AC-22A / AC-22B (400V AC)	100 A / 100 A
AC-22A / AC-22B (500V AC)	-
AC-22A / AC-22B (690V AC)	40 A / 40 A
AC-23A / AC-23B (400V AC)	63 A / 63 A
AC-23A / AC-23B (500V AC)	-
AC-23A / AC-23B (690V AC)	25 A / 25 A
-	-
-	-
-	-
-	-
-	-
-	-
-	-
-	-

MECHANICAL CHARACTERISTICS

Mechanical life	10.000 cycles
Maximum number of auxiliary contacts that can be installed	1
Minimum cable size	4 mm ²
Maximum cable size (rigid/flexible)	50 / 35 mm ²
Maximum busbar width	-
Rated tightening torque	6 Nm
Pre-arrangement for lock in OFF position	Yes (ø6 mm max)
Height	94 mm
Width (mm)	215
Depth	50 mm
Weight (kg)	1.2
DC RATED OPERATIONAL CURRENT (Ie)	
DC-20A / DC-20B (220V DC)	100 A / 100 A (2 poles in series for each polarity)
DC-20A / DC-20B (400V DC)	-
DC-20A / DC-20B (440V DC)	-
DC-20A / DC-20B (500V DC)	-
DC-21A / DC-21B (220V DC)	100 A / 100 A (2 poles in series for each polarity)
DC-21A / DC-21B (400V DC)	-
DC-21A / DC-21B (440V DC)	-
DC-21A / DC-21B (500V DC)	-
DC-22A / DC-22B (220V DC)	100 A / 100 A (2 poles in series for each polarity)
DC-22A / DC-22B (400V DC)	-
DC-22A / DC-22B (440V DC)	-
DC-22A / DC-22B (500V DC)	-
DC-23A / DC-23B (220V DC)	63 A / 63 A (2 poles in series for each polarity)
DC-23A / DC-23B (400V DC)	-
DC-23A / DC-23B (440V DC)	-
DC-23A / DC-23B (500V DC)	-

DIMENSIONAL



Product Data Sheet

GW97760

97 MSS Range

STANDARDS/APPROVALS

