



Description Interruttore automatico scatolato
 Code MSX 250c
 No. of poles 3P
 Rated current 160 A
 Release Electromechanic

ELECTRICAL CHARACTERISTICS

| | |
|---|----------------------|
| Standard | IEC/EN 60947-2 |
| Use category | A |
| Rated frequency (Hz) | 50 / 60 |
| Rated operating voltage (Ue) | 525 Vac - 250 Vdc |
| Rated impulse withstand voltage (Uimp) | 8 kV |
| Overvoltage category | IV |
| Insulation voltage (Ui) | 800 V |
| Thermal regulation | 0,63 - 0,8 - 1 x In |
| Magnetic regulation | 6 - 8 - 10 - 13 x In |
| Neutral protection | - |
| Total power loss | 36.87 W |
| Rated short-circuit current making capacity (Icm) | - |
| Rated short-time withstand current for 0,3s (Icw) | - |
| I _{dn} regulation | - |
| DT regulation | - |

MECHANICAL CHARACTERISTICS

| | |
|-------------------------------------|----------------------------|
| Execution | Fixed |
| DIN rail mounting | Yes, by means of accessory |
| Can be equipped with motor operator | Yes |
| Compatible interlock | Lever - Cable |
| Terminals supplied | Front FC |
| Assembly position | Any |
| Upline/downline power supply | Yes |
| Electrical life (415Vac) | 6.000 cycles |
| Mechanical life | 18.000 cycles |
| Operating temperature | -5°C +65°C |
| Stocking temperature | -20° +65° |
| Weight (kg) | 1.5 |
| Width | 105 mm |
| Height | 165 mm |
| Depth | 68 mm |


SERVICE BREAKING CAPACITY (ICU)

| | |
|------------|-------|
| 220/240Vac | 25 kA |
| 400/415Vac | 16 kA |
| 440Vac | 10 kA |
| 525Vac | 6 kA |
| 690Vac | - |
| 250Vdc | 13 kA |

RATED BREAKING CAPACITY (ICS)

| | |
|------------|-------|
| 220/240Vac | 13 kA |
| 400/415Vac | 8 kA |
| 440Vac | 5 kA |
| 525Vac | 3 kA |
| 690Vac | - |
| 250Vdc | 7 kA |

DIMENSIONAL





Product Data Sheet

GWD9087

MSX

STANDARDS/APPROVALS

