





The widest range of flush-mounting switchboards and distribution boards available on the market today. Seven families designed to offer solutions in the residential and advanced tertiary sectors, also available in Halogen Free material. Versions from 2 to 72 modules, degrees of protection from IP40 to IP55 and specific versions also for plasterboard. Furthermore, the offer includes Multimedia Enclosures in compact (36 modules) and complete (54 modules) versions, both compliant with what is suggested by the CEI 306-2 guide.

Insulation class	II (according to IEC 61140 standards)	Colour	Varnished titanium
Outer dim. LxHxD (mm)	146x165x108	IP degree	IP40
Installation	Flush mounting enclosures	Dispersible power (W)	13
Mechanical resistance	IK08	Rated voltage	400 V
Door colour	Smoked Transparent	No. of modules EN 50022	4+1/2
Rated current	125 A	Glow Wire Test	650 °C
For walls	Brickwall	Operating temperature	-15 ÷ +60 °C
Type of material	Halogen-free in compliance with EN 60754-2	Thermo-pressure with ball	70 °C
Standard	EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49	Insulation voltage	750 V
Max. installable terminal blocks	-		



BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Not resistant	Limited resistance	Not resistant	Limited resistance	Limited resistance	Not resistant	Not resistant	Limited resistance	Limited resistance	Limited resistance

DIMENSIONAL



TECHNICAL SYMBOLOGY

 II (according to IEC 61140 standards)	IP IP40	IK IK08	GWT 650 °C	INSTALLATION  -15 ÷ +60 °C	HF HALOGEN FREE Halogen-free in compliance with EN 60754-2	 70 °C
--	-------------------	-------------------	----------------------	--	---	--

STANDARDS/APPROVALS

