






I-FAST products are JOINON's DC fast-charging solutions ideal for charging all types of electric vehicles equipped with high-voltage systems in private or public high-rotation parking lots, highways and service areas. The offer consists of wallboxes up to 30 kW and stations up to 180 kW. They feature an elegant design and finishes that make them an urban and extra-urban furnishing product, with a graphic display for a better User Experience and use of services for the EV Driver user.

Power specification - AC input		- Environmental		-
Input voltage	3 Φ 380 ± 415 Vac	Operating temperature		-30°C ÷ +50 °C
AC input connection	3P+N+PE (Wye configuration), TN/TT	Humidity		5% ÷ 95% RH, Non-Condensing
Max input current	3 Φ 86A	Altitude		≤ 2.000 m
Frequency	50 Hz / 60 Hz	IP degree		IP55
Power factor	> 0.99	Mechanical resistance	IK10 (not including screen & RFID module)	
Efficiency	>94%	Cooling method		Fan cooling
Power specification - DC output		- Mechanical		-
Output voltage range	CCS2: 150 ÷ 950 Vdc	Dimension		700 mm x 330 mm x 1.800 mm
Max output current	CCS2: 120A	Weight		235 kg
Maximum output power	60 kW	Cable length		4 m
Voltage/Current accuracy	±2%	Protection		-
User interface & control		- Input protection		OVP, OCP, OPP, OTP, UVP, RCD, SPD
Display	7" graphic	Output protection		SCP, OCP, OVP, LVP, OTP, IMD
Push buttons	Operation Buttons / Emergency Stop Button	Regulation		-
User Authentication	OCPP 1.6 JSON, QR Code, App	Accessibility		-
Meter	DC PTB Meter	Safety		CE, CB
Communication		- Certificate		IEC 61851-1, IEC 61851-23, IEC 61851-21-2
External	Ethernet, Wi-Fi and 4G	Charging interface		DIN 70121, ISO 15118-2
Internal	CAN bus / RS485	National		-
Contactless Solution		- -		-
Payment terminal	Yes, Payter P66			-

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IK

IP55

IK10 (not including screen & RFID module)

STANDARDS/APPROVALS

