Product Data Sheet
GW10720

Home&Building Pro



Breed assortiment van besturingsapparaten, contactdozen voor voeding (conform nationale en internationale normen), signaalontvangst, klimaatbeheersing, comfortbeheer, technische alarmsignalering en noodverlichtingsbeheer. De ChoruSmart modulaire apparaten zijn beschikbaar in vijf kleuren - glanzend wit, satijn wit, natuurlijk beige, satijn zwart en gelakt titanium - en in verschillende maten van 1/2, 1, 2 en 3 modules. Dankzij de montagesteunen voor rechthoekige, vierkante en ronde dozen kunnen eindeloze combinaties worden gecreëerd met de ChoruSmart-platen.

Omschrijving	Voeding	Kleur	Wit
Uitvoer voltage	12 V dc	Max. geleverde stroom	300 mA
IP graad	IP20	Standaard	EN 55015 - EN 61547 - EN 61000-3-2 - EN 61000-3-3
Bedradingsklemmen	Met schroef	Klem aandraaicapaciteit litzekabel (mm²)	min. 0,5 - max. 1,0
Klem aandraaicapaciteit kabel massieve kern (mm²)	min. 0,5 - max. 1,0	Afmetingen LxHxD (mm)	52x33x17
Electrocod	0510		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20

STANDARDS/APPROVALS

Reach Declaration

CE

GEWISS S.p.A. Via Domenico Bosatelli 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 19/09/2024

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice