



Dedicated emergency kit made in grey PC (RAL 7035) for Smart[3] through wiring version. Equipped with Ni-Mh batteries for 3h autonomy. Can be fitted on the unit itself using fixing springs or mounted on the wall/ceiling, using 4mm screws.

|                     |   |                       |                                   |
|---------------------|---|-----------------------|-----------------------------------|
| Gewicht (kg)        | 1.3   | Autonomie             | 3 h                               |
| Isolatie klasse     | II  | IP graad              | IP66                              |
| Voeding batterijen  | Vervangbaar                                 | Mechanische weerstand | IK08                              |
| Type                | Kit   | Voltage               | 220 - 240 V - 50/60 Hz            |
| Bevestiging         | Op het armatuur/aan de wand/aan het plafond | Omschrijving          | Smart [3] noodkit - via bedrading |
| Serie               | SMART [3]                                   | Toepassing            | Intern                            |
| Bedrijfstemperatuur | +5 +25 °C                                   | Laadtijd              | 24 u                              |
| Feedback laadstatus | Groene LED                                  | Garantie              | 5 jaar                            |
| Gloeidraadtest      | 850 °C                                      | Stroominvoer          | H07RN-F 4x1 mm2 kabel             |
| Stroomuitvoer       | 4P vrouwelijke GW-connector                 | Electrocod            | 2434                              |

## DIMENSIONAL

## PHOTOMETRIC DISTRIBUTION

## TECHNICAL SYMBOLOGY



**IP**

IP66

**IK**

IK08



**GWT**

850 °C

## STANDARDS/APPROVALS

