



Dedicated emergency kit made in grey PC (RAL 7035) for Smart[3] through wiring version. Equipped with Ni-Mh batteries for 3h autonomy. Can be fitted on the unit itself using fixing springs or mounted on the wall/ceiling, using 4mm screws.

Gewicht (kg)	1.3	Autonomie	3 h
Isolatie klasse	II	IP graad	IP66
Voeding batterijen	Vervangbaar	Mechanische weerstand	IK08
Type	Kit	Voltage	220 - 240 V - 50/60 Hz
Bevestiging	Op het armatuur/aan de wand/aan het plafond	Omschrijving	Smart [3] noodkit - via bedrading
Serie	SMART [3]	Toepassing	Intern
Bedrijfstemperatuur	+5 +25 °C	Laadtijd	24 u
Feedback laadstatus	Groene LED	Garantie	5 jaar
Gloeidraadtest	850 °C	Stroominvoer	H07RN-F 4x1 mm2 kabel
Stroomuitvoer	4P vrouwelijke GW-connector	Electrocod	2434

DIMENSIONAL

PHOTOMETRIC DISTRIBUTION

TECHNICAL SYMBOLOGY



IP

IP66

IK

IK08



GWT

850 °C

STANDARDS/APPROVALS

