



Description Interruttore automatico scatolato

Code MSX 160c

Nombre de pôles 3P

Courant nominal 160 A


Déclencheur Elettromeccanico

ELECTRICAL CHARACTERISTICS

MECHANICAL CHARACTERISTICS

Norme	IEC/EN 60947-2	Exécution	Fixe
Catégorie d'utilisation	A	Montage sur rail DIN	Si, tramite accessorio
Fréquence nominale (Hz)	50 / 60	Accessoriabile con comando motore	Non
Rated operating voltage (Ue)	525 Vac - 250 Vdc	Compatible inter-verrouillage	-
Tension nominale tenue à l'impulsion (Uimp)	8 kV	Equipé de cosses	FC avant
Catégorie de surtension	IV	Position de montage	Tout
Tension d'isolement (Ui)	690 V	Upline/downline power supply	Si
Réglage thermique	0,63 - 0,8 - 1 x In	Electrical life (415Vac)	10000 cycles
Réglage magnétique	Fixe - 1600 A	Durée de vie mécanique	20.000 cycles
Protection du neutre	-	Température d'utilisation	-5°C +65°C
Puissance dissipée totale	46.2 W	Température de stockage	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Poids (kg)	0.8
Rated short-time withstand current for 0,3s (Icw)	-	Largeur	75 mm
I _{dn} regulation	-	Hauteur	130 mm
DT regulation	-	Profondeur	68 mm
SERVICE BREAKING CAPACITY (ICU)		RATED BREAKING CAPACITY (ICS)	
220/240Vac	25 kA	220/240Vac	13 kA
400/415Vac	16 kA	400/415Vac	8 kA
440Vac	10 kA	440Vac	5 kA
525Vac	6 kA	525Vac	3 kA
690Vac	-	690Vac	-
250Vdc	13 kA	250Vdc	7 kA

DIMENSIONS





Fiche produit

GWD9027

Gamme MSX

NORMES ET HOMOLOGATIONS

