




Range of Watertight surface-mounting boards made in polyester material reinforced with fibreglass. In compliance with IEC 61439-1 (CEI 17/113), IEC 61439-2 (CEI 17/114), IEC 60670-1 (CEI 23/48), IEC 60670-24 (CEI 23/49) e IEC 62208 (CEI 17-87). Available in 7 sizes, transparent and black door versions with IP66 protection degree. Fast&Easy accessories, made in metal, allow the installation of modular devices and moulded-case circuit breakers up to 250A into the boards, reducing assembly times by up to 40%. Indicated for automation and distribution for indoor and outdoor applications.

| | | | |
|-----------------------------------|--|---------------------------------------|---|
| Insulation class | II | Colour | Grey RAL 7035 |
| Nominal dim. LxHxD (mm) | 250x300x160 | IP degree | IP66 |
| Characteristics | UV resistance (EN 62208) | Material | Polyester reinforced with fibreglass |
| Mechanical resistance | Bottom IK10 | No. locks | 1 |
| Dispersible power A (W) | 34 | Dispersible power B (W) | - |
| Glow Wire Test | 650 °C | Functional dim. LxHxD (mm) | 253x303x160 |
| Operating temperature | -25 +60 °C | Insulation voltage (Ui) | 1000 V |
| Type of material | Halogen-free in compliance with EN 60754-2 | Electrocod | 0321 |
| Thermo-pressure with ball | 200 °C | Standard | EN 61439-1, EN 61439-2, EN62208, EN 60670-1, IEC 60670-24 |
| Family | 46 QP | Maximum rated insulation voltage (Ui) | 690 V |
| Type of door | Transparent door | Surface-mounting brackets | GW46446-GW46451 |
| Kit for double insulation restore | GW46526 | | |

DIMENSIONAL



TECHNICAL SYMBOLOGY



II

IP

IP66



EN 62208
UV resistance (EN 62208)

IK

Bottom IK10

GWT

650 °C

HF

HALOGEN FREE
Halogen-free in compliance with EN 60754-2



200 °C

STANDARDS/APPROVALS



**UK
CA**

