



A complete system of IP65 boards for distributing energy in tertiary, commercial sector and building applications, available both empty and pre-wired, in accordance with the international standards EN 61439-3 and EN 61439-4. The distribution boards allow to house flush-mounting and interlocked socket-outlets up to 63 A and versions are available with 5, 10, 14 or 20 DIN modules and additional modules 14 and 20 DIN modules allow to increase modular space inside the boards. The switches can always be inspected, thanks to the wide transparent door with ergonomic handle and, thanks to the "hinged" screws of the front of the board, wiring and maintenance are easy. Q-DINs are ideal for fixed applications, surface-mounting or pole-mounting, and transportable applications, by handle and carrier. To ensure the best possible performance even in outdoor environments, prolonged exposure to the sun and bad weather, the boards are also UV resistant certified in compliance with EN 62208.

סוג	Q-DIN 5 DBO	סוג לוח	מחווט
צבע	RAL 7035 אפור	x גובה מידות חיצוניות אורך (מ"מ) עומק	105x340x120
(ק"ג) משקל	1.3	לפי התקנים	EN 61439-3 (DBO)
מאפיינים	עמידות לאולטרה-סגול (EN 62208)	IP	IP44
זעזוע התנגדות	IK09	בדיקת תיל לוחט	850°C (650° - אקטיביים) (חלקים פסיביים)
לחץ תרמי עם כדור	70 °C	class בידוד	II
ספק כוח	פס צבירה	מס' של קטבים	2P+E
הספק ניתן לאספקה (kW)	3	מפסק ראשי	AC דגם - 1RCBO 16A 2P 6 kA 0,03A
הגנה על מעגלים	MCB	מספר שקעים	2
2P+E שקע	1	10/16A שקע צ'קו	1
16A - IEC 309			

DIMENSIONAL


TECHNICAL SYMBOLOGY



IP
IP44

IK
IK09

GWT
850°C חלקים C (650° - אקטיביים) (חלקים פסיביים)



STANDARDS/APPROVALS

