Product Data Sheet

GWJ3604T


JOINON





I-CON EVO wallboxes are JOINON solutions designed to integrate into private and semi-public scenarios in accordance with the international standard IEC 61851-1 ed. 3. They are distinguished by both an elegant and compact design and special "one-hand charge" functionality. At the same time, the presence of a vandal-proof socket and IP55 degree combined with IK11-certified mechanical strength make them safe and reliable solutions. In addition, I-CON EVO wallboxes feature full connectivity to support the related JOINON EVO App for full and easy control of charging, intelligent management of loads and additional energy produced by any photovoltaic panels (also in Master/Slave mode), and several installation options: wall-mounted, flush-mounted, or floor-mounted.

Charging way	3 מוד	Charging sockets	2סוג
Connector type	Fixed socket (IPxxD)	Cable length (if available)	-
Electrical and Mechanical Characteristics	-	פסי צבירה	5x16 ממ"ר
Nominal tension	400 V	Total Maximum Current	ß2 A
הספק מקס'	22 kW	User protection	DC Leak 6mA
מד	-	התקנה	Wall / Flush / Floor mounting
חומר	POST-INDUSTRIAL recycled material	IP	IP55
		דרגה	
זעזוע התנגדות	IK11	טמפרטורת עבודה	מ-††25°C עד 55°C+55°C
Functional characteristics	-	קישוריות	Wifi+Ethernet
תקשורת	OCPP 1.6J	Load Management	DLM/PV BOOST
הפעלת טעינה	RFID או APP	ממשק אנושי	ίτ
Master/Slave	cl	"Over-the-air" updates	cl
Programmable Remote Contact	cl	Local directives	-
Accessories available	-	ערכת DLM CT	GWJ8037† חד-פאזי / GWJ8038 / תלת-פאזי
		להתקנה ארגונית	
Flush mounting backbox	GWJ8101	Single-sided floor support	GWJ8102
Double-sided floor support	GWJ8103	Protective cover	-
RFID Card	GWJ8002	4G modem kits	GWJ8111

DIMENSIONAL







TECHNICAL SYMBOLOGY

IP IK

P55 IK11

STANDARDS/APPROVALS

€