### **Product Data Sheet**

# **GWJ3704T**


#### **JOINON**




I-CON EVO wallboxes are JOINON solutions designed to integrate into private and semi-public scenarios in accordance with the international standard IEC 61851-1 ed. 3. They are distinguished by both an elegant and compact design and special "one-hand charge" functionality. At the same time, the presence of a vandal-proof socket and IP55 degree combined with IK11-certified mechanical strength make them safe and reliable solutions. In addition, I-CON EVO wallboxes feature full connectivity to support the related JOINON EVO App for full and easy control of charging, intelligent management of loads and additional energy produced by any photovoltaic panels (also in Master/Slave mode), and several installation options: wall-mounted, flush-mounted, or floor-mounted.

Charging way	8 алт	Charging sockets	20اډ
Connector type	Fixed socket (IPxxD)	Cable length (if available)	-
Electrical and Mechanic	al Characteristics -	-	-
פסי צבירה	5x16 ממ"ר	Nominal tension	400 V
Total Maximum Current	ß2 A	הספק מקס'	22 kW
User protection	DC Leak 6mA	מד	Meter MID
התקנה	Wall / Flush / Floor mounting	חומר	POST-INDUSTRIAL recycled material
IP	IP55	זעזוע התנגדות	IK11
דרגה			
טמפרטורת עבודה	מ-£25°C עד +55°C אעד +55°C	-	-
Functional characteristi	cs -	-	-
קישוריות	Wifi+Ethernet	תקשורת	OCPP 1.6J
Load Management	DLM/PV BOOST	הפעלת טעינה	RFID או APP
ממשק אנושי	לד	Master/Slave	q
"Over-the-air" updates	q	Programmable Remote Contact	Cl
Local directives	-	-	-
Accessories available	-	-	-
DLM CT KIT for load man	agement GWJ8038⁺ תלת-פאזי /	Single-sided floor support	GWJ8102
(	GWD6809+GWD6821+C.T. (GWD96441÷GWD96447) מעל		
	100A		
Flush mounting backbox	GWJ8101	Double-sided floor support	GWJ8103
Protective cover	-	RFID Card	GWJ8002
4G modem kits	GWJ8111		

#### **DIMENSIONAL**







## **TECHNICAL SYMBOLOGY**

IP IK

P55 IK1

# STANDARDS/APPROVALS

CE