



Wall-mounting thermostat to control heating/cooling and humidification/dehumidification systems and manage the temperature in manual mode or on 3 levels (comfort, pre-comfort, economy). Control algorithms for two-way systems: two points (ON/OFF), proportional integral (PWM). Includes 2 output contacts for heating, cooling or humidity control. Includes 1 input for external NTC temperature sensor (for room temperature measurement compensation or for underfloor heating protection). Equipped with a user interface with touch controls (capacitive) on technopolymer plate and backlit display. The thermostat has built-in proximity, temperature and humidity sensors and a Wi-Fi interface for setting parameters and programming temperature profiles (timed thermostat function) locally or remotely via specific apps (smartphone and tablet).

The device can be used:

- as an independent intelligent thermostat (in a stand-alone way), i.e. without the need for a Smart Home system, in this case the configuration and control of the device takes place via the "ThermoICE 2.0" APP;
- integrated into the Gewiss "Connected Smart Home" system, in this case the device can interoperate with all the other devices of the "Connected Smart Home" system and is configured and controlled together with all the other functions of the system via the "Home Gateway" APP.

Wall-mounting installation with wall-plugs or on 3-modules rectangular boxes (centre distance 83.5 mm).

Equipped with front plate. Plate material: technopolymer.

kategoria	Termostaty Ice Thermo	Komunikacja	Wifi
Kolor	Natural beige	Materiał	Front plate in technopolymer
Montaż	Montaż naścienny	Układ zasilania	110-230V ac - 50/60Hz
Current absorbed by power supply	< 3 W (in stand-by < 1 W)	Interfejsy	Wi-Fi 2.4GHz IEEE 802.11 b/g/n
Zmierzone rozmiary	Temperature, humidity, one additional input for external NTC temperature sensor	Liczba wyjść wejściowych	2 NO potential free
Napięcie Styki	Max switching current at 250Vac: 6A (cosΦ = 1); 1,5A (cosΦ = 0,6)	Liczba kanałów wejściowych	1 for external NTC sensor (type: NTC 10K, es. GW 10 800)
wejście wyjściowe	-	Zaciski okablowania	Ze śrubą
Zakres dokręcenia zacisku przewody elastyczne (mm <sup>2</sup> )	Max 1,5 mm <sup>2</sup>	Zakres dokręcenia zacisku przewody sztywne (mm <sup>2</sup> )	Max 1,5 mm <sup>2</sup>
Długość Temperatury	-5 ÷ +45 °C	Wilgotność względna (bez kondensacji)	Max 93%
Temperatura przechowywania	-25 ÷ +70 °C	Wymiary LxHxD (mm)	123,2x95,2x20,6
Ochrona IP	IP20	Norma	Directive RoHS 2011/65/EU + 2015/863 Directive RED 2014/53/EU EN 60730-2-9; EN 60730-2-7; EN 60730-1; EN 301 489-1; EN 301 489-17; EN 300 328; EN IEC 63000

## DIMENSIONAL

## TECHNICAL SYMBOLOGY

### IP

IP20

STANDARDS/APPROVALS

