

Product Data Sheet

GW20246


Seria 90 AM



The System modular devices make it possible to create infinite combination between devices and plates, thanks to a complete range that is able to satisfy all design, functional and installation requirements. Colour and finiture: glossy white, bright and versatile
Ideal for flush-mounting solutions (for rectangular or square boxes), surface-mounting solutions, and for special applications. The range includes commands, socket- outlets, protection, indicators, connectors and devices for the control, safety and comfort of your home.

kategoria	Zasilania	Opis	2P+E - 16 A, gniazdo na dwa rodzaje wtyczek
Kolor	Biały	wyjściowe	250 V ac
Przepust uziemiający	Boczny i środkowy	Norma	Włoski / Niemiecki
Charakterystyka	Z osłonami przed dziećmi	Do sworznie wtyczki	Ø 4 / 4.8 / 5 mm
Zaciski okablowania	Ze śrubą	Typ	P40
Norma	CEI 23-50 / IEC 60884-1	Rezystancja przy napięciu probierczym	2000 V przy 50 Hz przez 1 minutę
Wydłużona praca (liczba zmian położenia)	10,000 przy In 250 V AC cosφ=0,8	Twardość kulkowa	125 °C
Próba rozżarzoną drutem	850 °C	Uchwyt zacisku na trakcji kablowej	> 50 N
Zakres dokręcenia zacisku przewody elastyczne (mm²)	min. 0,75 - maks. 2x4	Zakres dokręcenia zacisku przewody sztywne (mm²)	min. 0,5 - maks. 2x2,5
Liczba SYSTEM Moduły	2	Materiał	Technopolimerowy
Electrocod	0131		

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

