

Product Data Sheet

GWD9156

MSX Range



Opis Interruttore automatico scatolato

Kod MSX 125

Liczba biegunów 3P

Prąd roboczy 125 A


zwolnienie Elettromeccanico

ELECTRICAL CHARACTERISTICS

ELECTRICAL CHARACTERISTICS		MECHANICAL CHARACTERISTICS	
Norma	IEC/EN 60947-2	Wykonanie	Fisso - Rimovibile
Zastosowanie kategoria	A	DIN rail mounting	Si, tramite accessorio
Prąd częstotliwość (Hz)	50 / 60	Accessorabile con comando motore	Si
Rated operating voltage (Ue)	690 Vac - 250 Vdc	Compatible interlock	Lever - Cable
Znamionowe wytrzymałwane napięcie impulsowe (Uimp)	8 kV	Terminals supplied	Przód FC
Przebiecie kategoria	IV	Montaż położenie	Wszelkie
Napięcia izolacji (Ui)	800 V	Upline/downline power supply	Si
Thermal regulation	0,63 - 0,8 - 1 x In	Electrical life (415Vac)	30.000 cycles
Magnetic regulation	6 - 8 - 10 x In	Mechanical life	30.000 cycles
Neutral protection	-	Temperatura robocza	-5°C +65°C
Total power loss	29.52 W	Temperatura przechowywania	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Masa (kg)	1.1
Rated short-time withstand current for 0,3s (Icw)	-	Szerokość	90 mm
Idn regulation	-	Wysokość	155 mm
DT regulation	-	Głębokość	68 mm
SERVICE BREAKING CAPACITY (ICU)		RATED BREAKING CAPACITY (ICS)	

220/240Vac	85 kA	220/240Vac	85 kA
400/415Vac	65 kA	400/415Vac	36 / 33 kA
440Vac	50 kA	440Vac	25 kA
525Vac	25 kA	525Vac	22 kA
690Vac	6 kA	690Vac	6 kA
250Vdc	40 kA	250Vdc	40 kA

DIMENSIONAL



Product Data Sheet

GWD9156

MSX Range

STANDARDS/APPROVALS

