





The wall-mounted I-ON charging stations are the JOINON solutions for public and semi-public access, designed for charging electric vehicles and to withstand any wear including impacts, stress, vandalism and atmospheric agents. They are the first and only on the market guaranteed with a IP55 protection rating. The special design allows the units to be adapted into any urban context and parking configuration, with a targeted focus on the user experience of drivers. They are available with standard JoinOn graphics, which may be customised on request.

| | | | | |
|-----------------------|----------------------------------|--------------------------------------|---------------------------------|---|
| INPUT | | | - Socket/Connector Nr. (Type) | 2 (Type 2 vandal-proof socket, with shutters) |
| Terminal blocks | 2 x (3 x 10 mm ²) | Charging activation | Remotely managed, via OCPP 1.6J | |
| Rated current | 64 A | Human Interface | LED RGB and TFT Display | |
| Total power | 15 Kilowatt | Connectivity | LAN | |
| OUTPUT | | | - MECHANICAL FACTS | - |
| Rated voltage | 230 V | Mounting and installation | Wall mount | |
| Colour | Grey, Headboard RAL 7011 | Power max. | 7,4 kW per socket | |
| Material | Steel sheet | Thermal-magnetic protection | Currently not present | |
| External treatments | Anti-corrosion and anti-graffiti | Type of residual current protection | Currently not present | |
| IP degree | IP55 | Power meter | Yes (Type MID) | |
| Mechanical resistance | IK10 | DC Leakage check | Currently not present | |
| Operating temperature | -25 +50 °C | (Auto)restart electrical protections | Currently not present | |
| Customizations | Yes (front) | | | |

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP55

IK10

STANDARDS/APPROVALS

