






The wall-mounted I-ON charging stations are the JOINON solutions for public and semi-public access, designed for charging electric vehicles and to withstand any wear including impacts, stress, vandalism and atmospheric agents. They are the first and only on the market guaranteed with a IP55 protection rating. The special design allows the units to be adapted into any urban context and parking configuration, with a targeted focus on the user experience of drivers. They are available with standard JoinOn graphics, which may be customised on request.

<b>INPUT</b>		- Socket/Connector Nr. (Type) 1(Type 2 vandal-proof socket, with shutters) + 1(Type E)	
Terminal blocks	1 x (3 x 10 mm <sup>2</sup> ) + 1 x (3 x 6 mm <sup>2</sup> )	Charging activation	Locally managed, via RFID
Rated current	42 A	Human Interface	LED RGB and TFT Display
Total power	10 Kilowatt	Connectivity	No
<b>OUTPUT</b>		<b>- MECHANICAL FACTS</b>	
Rated voltage	230 V	Mounting and installation	Wall mount
Colour	Grey, Headboard RAL 7011	Power max.	7,4 kW per socket (2,3 kW for type E)
Material	Steel sheet	Thermal-magnetic protection	Currently not present
External treatments	Anti-corrosion and anti-graffiti	Type of residual current protection	Currently not present
IP degree	IP54	Power meter	Yes (Type MID)
Mechanical resistance	IK10	DC Leakage check	Currently not present
Operating temperature	-25 +50 °C	(Auto)restart electrical protections	Currently not present
Customizations	Yes (front)		

## DIMENSIONAL



## TECHNICAL SYMBOLOGY

**IP**

**IK**

IP54

IK10

## STANDARDS/APPROVALS

