



Description COMPACT MINIATURE CIRCUIT BREAKER

Code MTC 60

No. of poles 2P

No. modules 1

Rated current 20 A

Curve B

Rated voltage 230 V

|   |                                     |  |                                |
|---|-------------------------------------|--|--------------------------------|
| Standard                                    | EN 60898, EN 60947-2                | Rated frequency (Hz)                   | 50/60 Hz                       |
| Breaking capacity EN 60898 230V (Icn)       | 6000 A                              | Breaking capacity EN 60898 (Ics)       | 1 x Icn                        |
| Breaking capacity IEC/EN 60947-2 230V (Icu) | 10 kA                               | Breaking capacity IEC/EN 60947-2 (Ics) | 100% Icu                       |
| Insulation voltage (Ui)                     | 500 V                               | Rated impulse withstand voltage (Uimp) | 4 kV                           |
| Minimum operating voltage                   | 12V ac/dc                           | Maximum operating voltage              | 440V AC / 220V DC              |
| Electrical endurance                        | 10.000                              | Mechanical endurance                   | 20.000                         |
| Section rigid cable                         | <=1x16 - <=1x10+1x6 mm <sup>2</sup> | Section flexible cable                 | <=1x10 - <=2x6 mm <sup>2</sup> |
| Rated tightening torque                     | 1.2 Nm                              | Operating temperature                  | -25 +60 °C                     |
| Stocking temperature                        | -40 +70 °C                          | Electrocod                             | 1411                           |

### DIMENSIONAL



### STANDARDS/APPROVALS

