





Floodlight in die cast aluminum with galvanized bracket and painted the same color as the body. Equipped with graduate scale to facilitate orientation. Separated optical and electrical compartment. Front opening through manual hooks. Flat tempered glass 5mm thickness. Anti-aging silicone gasket. Power input through cable camp for cables $\varnothing 7 \div 10.5$ mm. Optic in 99.85% polished and anodised aluminium. Electrical component plate in galvanized steel. Tripolar terminal block. Wired version with power factor correction.

| | | | |
|---------------------------------------|---------------------------------|--|---------------|
| Application | External | IP degree | IP66 |
| Mechanical resistance | IK10 | Insulation class | I |
| Maximum surface exposed to the wind | 0.15 m ² | Minimum distance from the illuminated object | 1 m |
| Weight (kg) | 10.1 | Colour | Graphite grey |
| Voltage | 230 V - 50 Hz | Lamp power | 150 W |
| Lamp current | 1.8 A | Lamp holder | E40 |
| Lamp supplied | ST | Lamp included | Yes |
| Efficiency class of the lamp supplied | A+ | Efficiency class of compatible lamps | A+ |
| Optic | Symmetrical diffused - ULOR: 0% | Electrocod | 244B |

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



IP

IP66

IK

IK10



0.15 m²



1 m



WITH LAMP



STANDARDS/APPROVALS

