





Urban decorative in die-cast aluminum EN AB 46100 powder poliester painted after epoxy surface treatment and phosphochromating process, with lateral ventilation system by plastic grid. Recessed handle closing system and steel holding cable. External screw stainless steel AISI 316. Anti ageing silicone gasket. Double two poles safety knife for wires 2,5 mm². PC holding components plate. Internal wiring with UG4G4 1mmq wires. Modular LED engines (2-4) with injected aluminum heat sink equipped with PMMA lenses. Pole fixing system provided with Gewiss bracket. It can be used up to 50 ° C of ambient temperature but with reduced currents as indicated in the Technical Manual.

Insulation class	II	Colour	Graphite grey
IP degree	IP66	Mechanical resistance	IK08 BODY - IK06 LENS
Voltage	220/240 V - 50/60 Hz - Stand alone and/or possibility of dimmer 1-10 V	Weight (kg)	8.199999999999999
Series	URBAN [O3]	Application	External
Number of modules	2 (2x16 LED)	Optic	Street - ULOR: 0%
Maximum surface exposed to the wind	0.25 m ²	Minimum distance from the illuminated object	1 m
Suitable for	Gewiss side brackets	System power	54 W
Lumen output (lm)	3460	Colour temperature	3500 K (CRI>85)
Voltage	220-240 V - 50/60 Hz	LED current	530mA
Warranty	5 years	Operating temperature	-25 +35 °C
Driver type	Constant Current Driver Led	Type of lamp	LED
Electrocod	244C	Photobiologic Risk	RG1/RG2 @ 20cm
Nominal flux (lm)	3940	LED Life Time (L80B10)	100000 h
LED Life Time (L90B20)	50000 h	Overvoltage resistance	Common mode: 4KV; Differential mode: 3KV

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



IP

IP66

IK

IK08 BODY -
IK06 LENS



CONSTANT
CURRENT
DRIVER



0.25 m²



1 m



5 YEARS
WARRANTY



INSTALLATION
min 26 °C
max +38 °C

STANDARDS/APPROVALS

