Product Data Sheet

GW84204

La cerere

Proiectoare multifuncționale din aluminiu turnat, vopsite cu pulbere de poliester, pentru utilizări portabile pe suport tubular Componente optice din aluminiu 99,85 % lustruit şi anodizat Sticlă călită plată, grosime 5 mm Garnitură din silicon anti-îmbătrânire Adecvat pentru utilizarea cu lămpi de halogen Echipat cu carcasă de protecție şi cablu de tip H07RN-F cu secțiune de 3 x 1,5 mm², lungime de 5 m cu fişă IEC 309 2P+E 200-250 V IP67

Cerere	**Interior - Exterior**	**Tipul de utilizare**	**Instrumentele**
Grad IP	**IP55**	**Rezistență mecanică**	**IK10**
Clasa de izolație	**I**	**Distanța minimă față de obiectul iluminat**	**1 m**
Greutate (kg)	**2.8**	**Culoare**	**Gri grafit**
Curent lampă	**2.1 A**	**Putere max lampă**	**500 W**
Suport lampă	**R7s**	**Lampă**	**HD**
Clasa de eficiență a lămpilor compatibile	**„D + C:**	**Optică**	**Optică simetrică - ULOR: 0%**
Electrocod	**2424**		

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY

IP IP55

IK IK10

1 m

STANDARDS/APPROVALS

CE

Data, measures, designs and pictures are for information purpose only, last update 26/04/2024. They can be changed at any moment, therefore it is always ecommended to read the last updated version published on the website www.gewiss.com.Lumen output and system power are subject to a tolerance of +/- 10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C. Terms of warranty at https://www.gewiss.com/it/en/company/landingpage/led-warranty. -